



12.8V 200Ah LiFePO₄ Battery

Model: W-B200

FEATURES

- Longevity of service
- IP65 waterproof and dustproof
- Flame retardant rating: UL94 V-0 (Plastic shell)
- Green energy without metal contaminant
- Extremely high number of charge / discharge cycles
- Lightweight, small size
- In the extreme performance safety test, the battery will not catch fire, explode, or leak, and will be safer to use
- Sophisticated Battery Management System (BMS)



BMS OPERATION

Typical Charging Current	50A
--------------------------	-----

Maximum Charging Current	100A
--------------------------	------

Typical Discharge Current	50A
---------------------------	-----

Maximum Discharge Current	100A
---------------------------	------

Maximum Charge Voltage(CC/CV)	14.4V
-------------------------------	-------

Over Charge Protection

Voltage(Cell)	3.75V±0.03V
---------------	-------------

Delay Time	1000ms±500ms
------------	--------------

Recovery Voltage(Cell)	3.55V (Min 3.40V, MAX 3.60V)
------------------------	------------------------------

Over Discharge Protection

Voltage(Cell)	2.20V±0.08V
---------------	-------------

Delay Time	1000ms±500ms
------------	--------------

Recovery Voltage(Cell)	2.70V±0.10V
------------------------	-------------

Over Discharge Protection Release Conditions	Disconnect load or charge release
--	-----------------------------------

Over-Current Charge

Primary Charge Over Current Protection Value	180A±50A
--	----------

First Stage Charge Over Current Delay	1000ms±500ms
---------------------------------------	--------------

Over-current Charge Release Conditions	Disconnect the charger
--	------------------------

Over-Current Discharge

Primary Discharge Over Current Protection Value	900A±200A
---	-----------

Primary Discharge Over Current Protection Delay	10ms±5ms
---	----------

Secondary Discharge Over Current Protection Current Value	1800A±400A
---	------------

Secondary Discharge Over Current Protection Delay	1000us±500us
---	--------------

Over-current Discharge Release	Disconnect load or charge release
--------------------------------	-----------------------------------

Short Circuit

Short Circuit Protection Value	3600A±600A
--------------------------------	------------

Short Circuit Protection Delay Time	200μs-800μs
Short Circuit Protection Recovery	Disconnect load or charge release

Discharge High Temperature Protection

Temperature Protection Value	167°F±9°F / 75°C±5°C
Temperature Protection Release Value	136.4°F±9°F / 58°C±5°C

Charging High Temperature Protection

Temperature Protection Value	129.2°F±9°F / 54°C±5°C
Temperature Protection Release Value	120.2°F±9°F / 49°C±5°C

Charging Low Temperature Protection

Temperature Protection Value	32°F±9°F / 0°C±5°C
Temperature Protection Release Value	41°F±9°F / 5°C±5°C

High Temperature Protection Of FET(Built-in)

Temperature Protection Value	179.6°F~208.4°F / 82°C~98°C
Temperature Protection Release Value	122°F~176°F / 50°C~80°C

Balance Function

Equalizing Opening Voltage	3.50V±0.05V
Min Balance Current	150mA
Max Balance Current	250mA
Operation Temperature	-4°F~167°F / -20°C~75°C
Storage Temperature	23°F~104°F / -5°C~40°C (Humidity below 70%, time ≤ 1 year)

Heating Function

The voltage of the charger must be greater than 1V compared to the battery voltage. When the charging low temperature protection is reached, the heating is turned on. When the temperature reaches the charging low temperature protection release value, the heating is turned off.

SPECIFICATIONS

Battery Type	LFP Battery
Nominal Voltage	12.8V
Nominal Capacity	200Ah
Minimum Capacity	200Ah
Nominal Energy	2560Wh
Charging Voltage	14.4V
Discharging Cutoff Voltage	11.2V
Standard Charging Current	50A
Maximum Charging Current	100A
Standard Discharge Current	50A
Continuous Discharge Current	100A
Maximum Discharge Current	100A
Shell Material	Plastic Shell
Weight	About 48.5lb/22.0kg
Initial AC (1000HZ) Internal Resistance	≤50mΩ, New battery within 3 months, ACIR, 1000HZ
Monthly Self-Discharge Rate	≤5%
Overall Dimensions	20.9x8.1x8.5in
Cycle Life(Times)(77°F±3.6°F)	≥3200

Charging Temperature

30A	32°F~50°F / 0°C~10°C
50A	50°F~68°F / 10°C~20°C
100A	68°F~104°F / 20°C~40°C
30A	104°F~131°F / 40°C~55°C
Discharge Temperature	-4°F~140°F / -20°C~60°C (The surface temperature of the cell should not exceed 140°F)
Storage Temperature	-22°F~131°F / -30°C~55°C 90%RH Max (Less than 1 month) 14°F~113°F / -10°C~45°C 90%RH Max (More than 3 months)
Recommended Storage Temperature	14°F~95°F / -10°C~35°C 85%RH Max (Battery life decreases when stored in high temperature)

If the battery needs to be stored for a long time (more than 3 months), it should be stored in an environment which require temperature at a range of 14°F to 95°F (-10 to 35°C) @ 85% RH Max and no corrosive gases. It is recommended to charge and discharge the battery every 3 months and keep the SOC between 40~50%.